


N: HALF OF CONTACTS



RECOMMEND PCB LAYOUT(TOLERANCE=±0.05)

**1. MATERIAL**

- 1.1 INSULATOR: THERMOPLASTIC (UL 94V-0).
- 1.2 CONTACT MATERIAL: COPPER ALLOY.

**2. SPECIFICATION**

- 2.1 CURRENT RATING: 1.0 Amp.
- 2.2 INSULATION RESISTANCE: 500mΩ Min.
- 2.3 DIELECTRIC WITHSTANDING: 300VAC.
- 2.4 CONTACT RESISTENCE: 50mΩ Max.
- 2.5 OPERATING TEMPERATURE: -40°C TO +105°C.

**3. PLASTIC WITHSTAND TEMP**

- 3.1 MAX PROCESSING TEMP:  
 180°C FOR 30-60 SEC; (200°C FOR 5-10 SEC.) - PBT  
 230°C FOR 30-60 SEC; (260°C FOR 5-10 SEC.) - PA6T

**PH 127 - XXX - X X X GX**

**Gender**

- P=Pin Header
- F=Female Header

**Pitch**

- 0.80=080
- 1.00=100
- 1.27=127
- 2.00=200
- 2.54=254

**No. of PINS**

- 1 x 01 ~ 1 x 40 PINS
- 2 x 01 ~ 2 x 40 PINS
- 3 x 01 ~ 3 x 40 PINS

**Connector Type**

- S=Straight
- R=Right Angle
- M=SMT

**Plating (Standard: G0)**

- G0: Gold Flash
- G2: 1U" Gold
- G3: 3U" Gold
- G4: 5U" Gold
- G5: 10U" Gold
- G6: 15U" Gold
- SN: Tin

**Packing Style**

- 1. Loose in Bag
- 2. Tape & Reel
- 3. Tube

**Insulator Material**

- 1: PBT
- 2: PA6T
- 3: PA9T
- 4: LCP

PRODUCT TITLE:		1.27mm Pin Header, Thru-Hole, Right Angle, Dual Row		
UNLESS OTHERWISE SPECIFIED TOLERANCES	SCALE: 1/1	UNIT: mm		PH127-2XX-RXXG0-07
	SIZE: A3	PAGE: 1 OF 1	RAV.A01	
DECIMALS:	ANGLES:	<b>WAYCONN ELECTRONICS</b>		
X : ±0.5	X : ±6°			
X.X : ±0.3	X.X : ±3°			
X.XX : ±0.2	X.XX : ±2°			